

Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description
--------	----------------------

1000 PLT Launching unit without air cylinder and cover
 Launching Unit without air cylinder and cover.



1005 PLT Launching unit
 Launching Unit with air cylinder and cover.
 Contents:
 1 Art No 1306 Air Cylinder
 1 Art No 1000 Launching Unit
 1 Art No 1017 Cover for air cylinder



1006 PLT Launching unit US
 Launching Unit with air cylinder (certified for the US and Canadian market) and cover.
 Contents:
 1 Art No 1307 Air Cylinder
 1 Art No 1000 Launching Unit
 1 Art No 1017 Cover for air cylinder








1013 Firing valve







Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	
1017	Cover for air cylinder	
1021	Reduction valve complete	
1031	Safety valve	
1050	Complete set of packing and o-rings Packings and O-rings for the PLT Launching Unit	
1054	Hatch lock w. loop 2 pcs	
1303	Launching tube Rescue 230 Launching Tube for Rescue 230 projectile and the Art No 1005/1006.	





Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	
1306	<p>Air cylinder complete</p> <p>Air Cylinder w/ closing valve. 1,45 liter (50 fl oz). Work pressure 300bars/4350psi</p>	
1307	<p>Air cylinder US complete</p> <p>Air Cylinder w/ closing valve. 1,45 liter (50 fl oz), certified for the US and Canadian market. Work pressure 200bars/2900psi</p>	
1308	<p>Adapter 200/300 bar (Yoke-DIN477)</p> <p>Adapter for filling of the air cylinder from Yoke 200 bars (2900psi) standard.</p>	 
1309	Closing valve w/ manometer	
1310	<p>Air filling hose w/ connections</p> <p>Air filling hose with couplings and pressure releaser.</p>	





Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	
1502	Pivot support Used for a safer handling of the PLT. Fits into the Pivot Tube (Art No 1503).	
1503	Tube for pivot support Shall be welded at a convenient spot for launching the PLT.	
2000	PLT Rescue 230 complete PLT Rescue 230 complete according to IMO/Solas 74/83, Line Throwing apparatus. Contents: 1 Art no 1005 PLT Launching unit 1 Art no 1303 Launching Tube Rescue 230 4 Art no 2101 Projectile Rescue 230 1 Art no 2200 Loading Device 1 Art no 3303 Launching Tube 125/150 1 Art no 7004 Projectile PLT 150 1 Art no 6201 Linebox 5mm floating line 1 CD/User Manual Typical shooting range with a dry and clean line of 3,2mm(Art No 2103): 230m Breaking strength : 2000N USCoastGuard approval number 160.040/EC0575/6519	
2001	PLT Rescue 230 US complete Same as Art No 2000, certified for the US and Canadian market (Art No 1006 instead of Art No 1005). USCoastGuard approval number 160.040/EC0575/6519	




Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	
2101	<p>Projectile Rescue 230 Projectile for PLT Rescue 230. The line is stored inside the projectile. Made from ABS plastic and aluminum. The Rescue projectile must never be launched without the end plug (art No 2104). Typical shooting range with a dry and clean line of 3,2mm (Art No 2103): 230m Breaking strenght : 2000N</p>	
2103	<p>Safety line projectile Rescue 230 Safety Line for Art No 2101, 3.2mm. Comes on a spool of 250 meters. Breaking strength 2000N.</p>	
2104	<p>End plug for projectiles with internal line End plug for Projectile Rescue 230 (art no 2101), Projectile PLT 125 (art no 3101) and Projectile PLT Mini 100 (art no 4101). The projectile must never be fired without the end plug.</p>	
2105	<p>Line 2mm hollow braided Dyneema Safety Line for Art No 2101 or 4101, 2mm. Comes on a spool of 350 meters. Breaking strength 7800N.</p>	





Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Image
2200	<p>Loading device Projectile Rescue 230 Loading Device for Art No 2101, Projectile Rescue 230. Connect to a low pressure source, 5-8 bars/75-110psi, it will blow the safety line back into the projectile.</p>	
3101	<p>Projectile Rescue 150 The line is stored inside the projectile. Made from ABS plastic and aluminum. Typical shooting range with a dry and clean line of 3,2mm(Art No 2103): 150m Breaking strength : 200kg</p>	
3200	<p>Loading device projectile Rescue 150 Loading Device for Art No 3101, Projectile Rescue 150. Connect to a low pressure source, 5-8 bars/75-110psi, it will blow the safety line back into the projectile.</p>	
3303	<p>Launching tube 150 Launching Tube for Rescue 150 and PLT 150 projectiles.</p>	

Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	
4105	<p>Projectile PLT/Mini-Rescue bouy Projectile that contains an automatic inflatable life buoy. Will inflate within 2 sec. after entering the water. Can be used with PLT and PLT Mini. The inflator has an expiry date. Uses 33gram CO2 cartridge. Typical shooting range with a dry and clean line of 2mm (Art No 4110) with the PLT Mini: 80m. Breaking strength : 190kg Typical shooting range with a dry and clean line of 3,2mm(Art No 2103) with the PLT: 115m. Breaking strength : 200kg</p>	
4113	<p>Projectile-entering grapple 4 Titanium grapple with black plastic coating. For entering constructions. For more information ask for brochure, "Entering solutions".</p>	
4115	<p>Projectile-entering grapple 3 Titanium grapple with 3 tines that are barbed from centre to the tip. One tine can hold 2000kg at the centre and 350kg at the tip before bending. Black plastic coating. For entering constructions. Fits lines up to 9mm for direct climbing after launching. Can be used by PLT and PLT Mini Launching Unit.</p> <p>Typical shooting range with a dry and clean double line of 3,2mm (Art No 2103) by PLT: 64m Typical shooting range with a dry and clean double line of 3,2mm (Art No 2103) by PLT Mini: 29m Using 9mm Technora fibers single line and PLT: 37m Using 9mm Technora fibers single line and PLT Mini: 16m</p>	

Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	
5000	<p>PLT 150 complete Linethrower for mooring and general line transfer. Contents: 1 Art no 1005 PLT Launching Unit 1 Art no 3303 Launching Tube 150 2 Art no 7004 Projectile PLT 150 1 Art no 5202 Linebox 3,2mm nylon Other options of line on request 1 CD/User Manual. Typical shooting range with a dry and clean line with 3,2mm(Art No 2103): 140m Breaking strength : 200kg.</p>	
5001	<p>PLT 150 US complete Same as Art No 5000, certified for the US and Canadian market (Art No 1006 instead of Art No 1005).</p>	
5202	<p>Linebox 3,2 mm nylon Linebox containing 150m (164 yd) of 3,2mm (0.13 in) (Art No 2103) of line. Used for maximum range for projectile Art no 7004. Breaking strength : 200kg</p>	
6000	<p>PLT 75 complete Linethrower for mooring and general line transfer. Contents: 1 Art no 1005 PLT Launching Unit 1 Art no 6303 Launching Tube PLT 75 2 Art no 6101 Projectile Ball 1 Art no 6201 Linebox 5mm floating line Other options of line on request 1 CD/User Manual. Typical shooting range with a dry and clean line with 5mm (art no 6109): 90m</p>	

Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description
--------	----------------------

Breaking strength : 440kg.

6001	<p>PLT 75 US complete Same as Art No 5000, certified for the US and Canadian market (Art No 1006 instead of Art No 1005).</p>
------	---



6101	<p>Projectile Ball Ball projectile for PLT 75 complete. Filled with air and coolant preventing freeze. Typical shooting range with a dry and clean line of 5mm (art no 6109): 90m Breaking strength : 440kg.</p>
------	---








6102	<p>Line 5 mm braided nylon Line, 120m 5mm (131yd 0.2in) braided nylon. Breaking strength 600kg.</p>
------	--







6103	<p>Line 5 mm braided Dyneema Line, 100/120m 5mm (109/131yd 0.2in) braided Dyneema (HMPE). Breaking strength 2000kg. Floats and has very little elongation under stress.</p>
------	---








Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	
6109	<p>Line 5mm Polypropylene Line, 120m 5mm (131yd 0.2in) Polypropylene. Breaking strength 440kg. Floats and has a very bright yellow color.</p>	
6200	<p>Loading device complete for 5mm line Loading Device for 5mm line. Connect to a low pressure source, 5-8 bars/75-110psi, it will blow the safety line back into the linebox.</p>	
6201	<p>Linebox 5mm floating line Linebox containing line art no 6109, polypropylene (120m). Breaking strength 440kg. Floats and has a very bright yellow color.</p>	
6202	<p>Linebox 5 mm nylon line Linebox containing line art no 6102, nylon (120m). Line, 120m 5mm (131yd 0.2in) braided nylon. Breaking strength 600kg.</p>	
6203	<p>Linebox 5 mm HMPE Linebox containing line art no 6103, HMPE (100/120m). Breaking strength 2000kg. Floats and has very little elongation under stress.</p>	




Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Image
6303	<p>Launching tube PLT 75 Launching Tube for art no 6101. Typical shooting range with a dry and clean line of 5mm (art no 6109): 90m</p>	
6304	<p>Launching tube PLT 75 extended version Launching Tube for Ball projectile. Typical shooting range with a dry and clean line of 5mm (art no 6109): 110m</p>	
7002	<p>Projectile PLT-line pick-up grapple Closed grapple for line pick-up. The closed ends secures the line within the barbes. Made from Stainless Steel and plastic. Typical shooting range with a dry and clean line of 5mm (art no 6102): 85m</p>	
7003	<p>Projectile PLT 150-lightstick Floating plastic projectile with lightstick holder. 2 lightsticks included. Typical shooting range with a dry and clean line of 5mm (art no 6102): 90m of 3,2mm (art no 5202): 130m.</p>	

Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Image
7004	<p>Projectile PLT 150 Rubber tipped plastic projectile that floats. Used for general line transfer or as a training projectile. Typical shooting range with a dry and clean line of 5mm (art no 6109): 115m of 3,2mm (art no 2103): 140m.</p>	
7020	<p>Lightstick Orange, 5 min/10 pc. 5 minutes burning time with full effect. Comes as a 10-pack. Used with Art No 7003.</p>	
7021	<p>Lightstick Yellow, 30 min/10 pc 30 minutes burning time with full effect. Comes as a 10-pack. Used with Art No 7003.</p>	
7023	<p>Spare rubber tip For art no 4106 and 7004.</p>	
7032	<p>Repacking set Life buoy w/ CO2 Repacking set for life buoy Art No 7035 and Art No 4105. Includes inflator, strips and a 33gram CO2 cartridge. The inflator has an expiry date.</p>	

Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Image
7034	<p>Repacking set Life buoy without CO2 Repacking set for life buoy Art No 7035 and Art No 4105. Includes inflator and strips. The inflator has an expiry date.</p>	
7035	<p>Rescue Egg Rescue Egg containing an automatically inflatable life buoy. No line attached. Ideal for MOB when ship is moving. The cover acts as a sea anchor. The inflator has an expiry date. Uses 33gram CO2 cartridge.</p>	
7036	<p>Inflator for Rescue bouy The inflator has an expiry date. The inflator is for the art no 4105, 7035 and repacking set for life buoys..</p>	
7038	<p>Quick link ladder connector Minimum order amount 2. Using the optional Ladder Connector the spacing remains the same when joining two ladders (order 2 for the Single Rung Ladder or order 3 for the Double Rung Ladder). CE-EN 362.</p>	

Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description
--------	----------------------


7039 Ladder Single Rung 10m
10m, lightweight, noiseless, non conducting, contains no metal parts and presents no radar signal. Built for heavy duty military use in marine environment!
One end of the ladder has a single attachment point for fast and easy deployment. The other end has a two separate attachment points. You can use this side to put 2 ladders together (with the optional Ladder Connectors) or you can use this side to connect it to two separate anchor points to rig it slightly more stable. Single Rung 200mm width. Rung spacing: 30cm. Using the optional Ladder Connector (art no 7038) the spacing remains the same when joining two ladders (order 2 for the Single Rung Ladder).



7040 Ladder Single Rung 15m
15m, specifications same as art no 7039.

7041 Ladder Single Rung 20m
20m, specifications same as art no 7039.

7042 Ladder Double Rung 15m
15m, lightweight, noiseless, non conducting, contains no metal parts and presents no radar signal. Built for heavy duty military use in marine environment!
One end of the ladder has a single attachment point for fast and easy deployment. The other end has a two separate attachment points. You can use this side to put 2 ladders together (with the optional TAGS Ladder Connectors) or you can use this side to connect it to two separate anchor points to rig it slightly more stable. Double Rung 390mm width. Rung spacing: 30cm. Using the optional Ladder



Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description
--------	----------------------

Connector (art no 7038) the spacing remains the same when joining two ladders (order 3 for the Double Rung Ladder). The double rung version is faster, more stable and more comfortable to climb than the single rung version. Especially in situations where you must climb downwards.

7043	Ladder Double Rung 20m 20m, specifications same as art no 7042.
------	---





8000	Whale Tagger complete Whale tagger launcher: Includes: 1 art no 1308 Filling adapter 1 art no 1306 Air cylinder with closing valve 2 art no 1303 Launching tube 1 art no 9400 Storage container 1 Red Dot aiming device 1 Shoulder support with quick connection 1 Base unit complete with valves and gauge.
------	--




9001	Turbo oil 165 ml ,PRF 290/220 Lubricant, for keeping the line thrower in clean and in good working condition. Used ones a month. Acid and water free.
------	---



Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	
9002	Manometer w/ packing Spare manometer with packing for the air cylinder.	
9200	Storage container PLT 75/150 complete Water proof container in heavy duty plastic. Easy storage and easy handling. Fits PLT 75 and 150 models. There are wheels on the container for easy transportation. Air and water tight.It even floats in the water.Internal dim. 580x440x330 mm, External dim. 670x510x372mm. 84liter and 14kg. Colour orange.	
9300	Storage container PLT 125 complete Water proof container in heavy duty plastic. Easy storage and easy handling. Fits PLT 125 model. There are wheels on the container for easy transportation. Air and water tight. It even floats in the water. Internal dim. 765x485x305 mm, External dim. 860x560x330mm. 113liter and 16,5kg. Colour orange.	
9400	Storage container PLT Rescue 230 complete Water proof container in heavy duty plastic. Easy storage and easy handling. It even floats in the water. Fits PLT Rescue 230 complete. Internal dim. 1350x350x135 mm, External dim. 1410x415x159mm. 63,7liter and 12kg. There are wheels on the container for easy transportation. Colour black.	

Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description	Image
9401	<p>Storage container PLT Mini, 75, 125 and 150 Water proof container in heavy duty plastic. Easy storage and easy handling. It even floats in the water. Fits PLT Mini, 75, R125 and 150 complete. Internal dim. 939x352x137 mm, External dim. 989x415x157mm. 45liter and 8kg. There are wheels on the container for easy transportation. Colour black.</p>	
9500	<p>Storage container deep Water proof container in heavy Duty plastic. Easy storage and easy handling. It even floats in the water. Internal dim. 1350x350x272 mm, External dim. 1410x415x296mm. 128,5liter and 16kg. There are wheels on the container for easy transportation. Colour black.</p>	
9900	<p>Bauer Kompressoren PE100-TE 3 phase 100l/min, 400V 50Hz. Delivery time is 3 weeks from ordering. 230V or 60Hz can be ordered with a delivery time of 6 weeks. The price will increase by NOK 1000,-. Dimensions is 89x50x49cm and 40kg.</p>	
9901	<p>Bauer Kompressoren PE100-TW Single phase 100l/min, 400V 50Hz. Delivery time is 3 weeks from ordering. 230V or 60Hz can be ordered with a delivery time of 6 weeks. The price will increase by NOK 1000,-. Dimensions is 89x50x49cm and 40kg.</p>	

Price in NOK ExWorks Restech Norway AS(incoterms 2010) and exVAT.

Art No	Name and description
--------	----------------------

9902	Bauer Kompressoren PE100-TB 4-stroke petrol 100l/min, 4,2 kW, 5,7 Hp. Delivery time is app 2 weeks from ordering. Dimensions is 89x50x49cm and 42kg.
------	---



9903	Bauer Kompressoren Junior II, 3 phase Compact Line Junior II 100l/min, 400V 60Hz. 230V is an option. Delivery time is 1-3 weeks from ordering. Dimensions is 66x36x42cm and 46kg.
------	--

